DF 5100
Droplet Separator



EQUIPMENT

DF 5100

- High separation efficiency
- Extremely thin design (90 mm)
- Very low pressure drop leading to lower operating costs
- Corrosion resistant
- Very easy installation
- Low maintenance cost due to simple operating principle and long lifetime
- Wide face velocity range
- Tailor made sizes and designs
- Hygienic design
- Wide range of highest quality material
- In house ISO 9001 certified manufacturing

DF 5100 is a ready-to-install droplet separator for use in many application areas. It is available in stainless steel and aluminium combinations and configurations to fit a wide range of operating conditions.

DF 5100 droplet separator provides high efficiency droplet separation and extreme low pressure drop even at medium face velocities giving energy saving operation.

The droplet separator can be configured to most individual performance and installation situations, providing a cost effective solution. Alternative material choices and drainage systems, as well as add-on features like flanges and protection mesh are just some of the configuration options.


DF 5100 droplet separator is a basic choice for keeping rain, mist and larger fog water droplets out of a building or marine ventilation system. This helps to reduce corrosion, to increase filter lifetime and to reduce moisture throughout the system.

DF 5100 droplet separator is designed for use in many applications and for an easy integration into the superstructure. The unit is suitable for use at face velocities in between 1 to 5.0 m/s at low liquid loadings.

Separation technology

The streamlined separator deflects the droplet laden gas stream; as a result the momentum of the droplets causes them to impinge onto the profile surface. The droplets coalesce together and form a liquid film; the influence of gravity causes the liquid to drain to the bottom of the profiles. Specially shaped separation chambers improve performance by enhancing the separation of finer droplets and ensuring problem free discharge of liquid.

To avoid “flooding” of the profiles and the possibility of re-entrainment of the separated liquid, the height of the profile sections, droplet separators is normally limited to 2,500 mm.



Principle illustration.


Munters

Performance


The limit drop size represents a performance characteristic of the profile, at the relevant velocity and operating conditions it is the size of the smallest droplet that is completely separated. The diagram showing limit drop size has been calculated for an air/water system at 20 °C and 1 bar.

The pressure drop is measured at ambient conditions (20 °C and 1 bar) through a number of assembled profiles under ideal conditions.

Limit drop size – DF 5100



Pressure drop DF 5100



For any data outside the specified range, please contact your nearest Munters representative.


Liquid load

The liquid removal capacity is fully sufficient for removing rain and spray completely under even harsh weather conditions.

Type, material and dimension specifications

Type code	Material		Width** A mm min–max	Height*** B mm min–max	Depth C mm	Operating temp °C min–max
	Frame*	Profile				
9l	316L	316L	300–2,500	300–2,500	90	–
9s	316Ti	316Ti	300–2,500	300–2,500	90	–

316L = Stainless steel (AISI 316L, DIN 1.4404)
316Ti = Stainless steel (AISI 316Ti, DIN 1.4571)




* *All frames can be painted on request (specify RAL code). All frames powder coated on request. All frames can be brushed to give a frosted appearance, stainless steel can be obtained polished.*

** *Standard tolerance on width and height: +0, –5 mm. Materials specified are standard – other materials on request).*

Drainage positions


Code for drainage position, put P before the position number, e.g., P9 or P6,8,9,10 if more outlets are to be used.



**Diameter of bushing, nipple or tube. Dimensions in mm.*

⑫ *Slot throughout the entire bottom for use with separate housing/tray.*

Drawing for fittings (see next page).




Fittings specifications

For stainless steel frames


Bushing Inside threads, both sides.

Fitting code	Ø inch	L mm
B1	1/2	34
B2	3/4	36
B3	1	43
B4	1 1/2	48
B5	2	56
B6	2 1/2	70
B7	3	95



Half bushing Inside threads, both sides.


Fitting code	Ø inch	L mm
C1	1/2	15
C2	3/4	17
C3	1	19
C4	1 1/2	22
C5	2	26






Weld-on nipple External threads, one side.


Fitting code	Ø inch	L mm
D1	1/2	35
D2	3/4	40
D3	1	40
D4	1 1/2	50
D5	2	50
D6	2 1/2	60
D7	3	65





Nipple* External threads, entire length.


Fitting code	Ø inch	L mm
E1	1/2	25
E2	3/4	40
E3	1	35
E4	1 1/2	38
E5	2	45






Bushing according to DIN 2986, nipples DIN 2982, material 316Ti (AISI 316Ti, DIN 1.4571), witworth – thread according to DIN 259.
** In combination with bushing (fitting code B).*

N.B. The required cross-section of the water outflow depends on both application and liquid load. Most frequently used fitting sizes are 3/4" and 1" and corresponding tube sizes.



Hole configurations in flanges are delivered according to Eurovent, DIN 24193, Norsok or other trade, national or international standards (specify standard). Hole configuration according to individual requirements are also delivered (specify drill pattern and hole diameter, provide drawing or use sketch on last page).




N.B. Depths [C] is the same with or without flanges.

Code	[mm] min–max
R	50–500



Code for radius, put R before the dimension, e.g. R150



Flanges specifications

Flange code		Position
Continous welded	Spot welded	
F1	F11	Top & bottom front
F2	F12	Left & right front
F3	F13	All sides front
F4	F14	Top & bottom back
F5	F15	Left & right back
F6	F16	All sides back
F7	F17	Top & bottom, front & back
F8	F18	Left & right, front & back
F9	F19	All sides front & back


Thickness*, T	
code	mm
T2	2
T3	3

Width*, W	
code	mm
W30	30
W50	50
W60	60

Material: Stainless steel in accordance with the frame material selected.
** Other thickness or width on request.*

Protection grid and mesh type specifications

Protection grid code	Position
G1	Front
G2	Back



Mesh width, S		Mesh type, wire diameter, d Ø [mm]			
inch	mm	1.0	1.2	1.5	2.0
1/4 × 1/4	5 × 5	Q1			
1/4 × 1/4	6 × 6	Q2	X2		
1/3 × 1/3	8 × 8	Q3	X3		
1/2 × 1/2	10 × 10	Q4	X4		
1/2 × 1/2	12 × 12	Q5		Y5	
3/4 × 3/4	16 × 16	Q6	X6	Y6	
3/4 × 3/4	20 × 20	Q7		Y7	Z7
1 × 1	25 × 25			Y8	Z8

Material: Stainless steel 304 (AISI 304, DIN 1.4301).
N.B. Protection grid is mainly used as trash screen on air inlets. Pressure drop over wire mesh is negligible.
Aluminium grids can be delivered on request.

DF 5100

DF 5100 droplet separator is developed to suit a wide range of applications. The various outfit options cover the most typically occurring installation variations. However, tailor made droplet separators are frequently delivered based on customers' individual specifications.

Material certificates can be delivered for most materials upon request. Fractional efficiency curves for given face velocities are delivered on special request.

For hygienic-proof HVAC equipment DF 5100 droplet separator can be delivered in accordance with the standards VDI 6022, VDI 3803, DIN 1946 (specify H in order code).

DF 5100 is developed and produced by Munters Euroform GmbH, Germany.

Order information


DF 5100-X-X-X-X-X-X-X-X-X-X-X

- Type code
- Width, mm
- Height, mm
- Drainage position(s) code
- Options
  - Fitting code
  - Flange position code
  - Flange thickness code
  - Flange width code
  - Protection grid position(s) code
  - Mesh type code
  - Radius code


e.g., DF 5100-8a-1820-1200-P9-A5-F2-T2-W30-G2-Q4-R150

Examples of installation

1. The droplet separator is flanged onto a wall opening and the water drains vertically outside of the wall.
2. The droplet separator is flanged into a wall opening and the water drains controlled into an internal tray (not shown in the drawing)
3. The droplet separator is installed in an air duct and stands in between angled profiles that are connected to the air duct. The water drains through the bottom into a tray that is below the air duct.
4. Galvanic separation of carbon steel structure from the mist eliminator (made of stainless or aluminium).



Drill pattern sketch



Munters, HumiCool Division, Kung Hans Väg 8, P.O. Box 434, SE-191 24 Sollentuna, Sweden. Phone +46 8 626 63 00, Fax +46 8 754 56 66.
Munters Euroform GmbH, Aachen, Germany. Phone +49 241 89 00 0, Fax +49 241 89 00 5199, munters@muntersac.de
Munters Corporation, Fort Myers, USA. Phone +1 239 936 1555, Fax 1 239 936 8858, moreinfo_me@americas.munters.com
www.munters.com

Australia Munters Pty Limited, Phone +61 2 6025 6422, Fax +61 2 6025 8266, **Austria** *via sales organization in Germany,* **Brazil** Munters Brasil Industria e Comercio Ltda, Phone +55 11 5054 0150, Fax +55 11 5054 0883, **China** Munters Air Treatment Equipment (Beijing) Co., Ltd., Phone +86 10 80 481 121, Fax +86 10 80 483 493, **Denmark** *via sales organization in Sweden,* **Finland** Munters Oy, Phone +358 9 83 86 030, Fax +358 9 83 86 0336, **France** Munters France S.A., Phone +33 1 34 11 57 50, Fax +33 1 34 11 57 51, **Germany** Munters Euroform GmbH, Phone +49 241 89 00 0, Fax +49 241 89 00 5199, **Indonesia** Munters, Phone +62 21 9105446-7, Fax +62 21 5310509, **Italy** Munters Italy S.p.A., Phone +39 0183-52 11, Fax +39 0183-521 333, **Japan** Munters K.K., Phone +81 3 5970 0021, Fax +81 3 5970 3197, **Kingdom of Saudi Arabia and Middle East** Hawa Munters, c/o Hawa United Cooling Syst. Co. Ltd., Phone +966 1 477 15 14, Fax +966 1 476 09 36, **Korea** Munters Korea Co,. Ltd, Phone +82 2 761 8701, Fax +82 2 761 8777, **Mexico** Munters Mexico Phone +52 722 270 40 30, Fax +52 722 270 41 95, **Norway** *via sales organization in Sweden,* **South Africa and Sub-Sahara Countries** Munters (Pty) Ltd, Phone +27 11 997 2000, Fax +27 11 608 3501, **Russia** Munters Europe AB, Phone: +7 812 4485740, Fax +7 812 5418660, **Spain** Munters Spain S.A., Phone +34 91-640 09 02, Fax +34 91-640 11 32, **Sweden** Munters Europe AB, Phone +46 8 626 63 00, Fax +46 8 754 56 66, **Switzerland** *via sales organization in Germany,* **Thailand** Munters (Thailand) Co. Ltd., Phone +66 2 645 2708-12, Fax +66 2 645 2710, **United Kingdom** Munters Ltd, Phone +44 845 644 3980, Fax +44 845 644 3981, **USA** Munters Corporation **Fort Myers**, Phone +1 239 936 1555, Fax +1 239 936 8858, Munters Corp. **Mason**, Phone +1 888 335 0100, Fax +1 517 676 7078, **Export & Other countries** Munters Europe AB, Phone +46 8 626 63 00, Fax +46 8 754 56 66.

Your closest distributor

Munters reserves the right to make alterations to specifications, quantities, etc., for production or other reasons, subsequent to publication.
© Munters, 2006

HC/MMA/EqGB-0715-11/06 pdf SGS ReklamStudio